

INDUSTRIAL CURTAIN SWITCHBOARD **STAVOKLIMA**
Installation and operation manual

UNIREG-ECO model





EN



1. Table of Contents

| | |
|--|---|
| 1. Table of Contents | 3 |
| 2. Safety measures | 4 |
| 3. Description of switchboard | 4 |
| 4. Function of the switchboard | 5 |
| 5. Operation of the switchboard | 5 |
| 6. Decommissioning – disposal | 5 |
| 7. UNIREG – ECO-A switchboard wiring scheme | 6 |
| 8. UNIREG – ECO EC switchboard wiring scheme | 7 |

Explanation of symbols used

| | |
|--|---|
|  <p>Instructions for mechanical repairs and maintenance.</p> |  <p>Important safety information, technical information, data and device output.</p> |
|  <p>Important electric information - read carefully - unit damage hazard in case of wrong installation.</p> |  <p>Important information - please read carefully.</p> |

2. Safety measures



The switchboard has been manufactured in line with the government decrees and Czech standards harmonized with the EU regulations mentioned in the manufacturer's declaration of conformity.

The above mentioned product complies with the following standards:

ČSN EN 60335-1 ed.3 ČSN EN 60335-2-30 ed. 3
 ČSN EN IEC 61000-6-2 ed. 4 ČSN EN 61000-6-3 ed. 2

The above mentioned product complies with the following directives:

- Directive 2009/125/EC of the European Parliament and of the Council establishing a framework for the setting of eco-design requirements for energy-related products.
- Government Decree No. 118/2016 Coll. Directive 2014/35/EU of the European Parliament and of the Council on the harmonisation of the laws of the Member States relating to the making available on the market of electrical equipment designed for use within certain voltage limits.
- Government Decree No. 117/2016 Coll. Directive 2014/30/EU of the European Parliament and of the Council on the harmonisation of the laws of the Member States relating to electromagnetic compatibility.
- Government Decree No. 481/2012 Coll. (Regulation of the European Parliament and of the Council No. 2014/35/EU, Regulation of the European Parliament and of the Council No. 2011/65/EU).
- Government Decree on restriction the use of some hazardous materials found in electrical and electronic products.

Observe generally applicable national provisions and other related regulations. Unplug the unit from mains before any service intervention. Connection and earthing of the electric device or components thereof must be in line with laws applicable in the country of use. Only qualified staff may carry out any electric service works.



Observe applicable laws, in particular:

- on safety of electric and thermal appliances,
- on central heat distribution systems,
- on fire safety.

3. Description of switchboard

- suitable for wall-mounting,
- designed to control hot water Stavoklima air units with 230V AC or EC fans,
- the switchboard is fitted with ECON TR or ECON EC controller,
- electric components for curtain control with accessories housed in plastic cabinet with ventilation holes,
- fitted with circuit breakers and performance components,
- the switchboard needs to be operated with ECON controller; otherwise, it is not operational.

| Type of control | UNIREG – ECO-A | | | | UNIREG – ECO EC |
|--------------------------------------|----------------|-----|-----|------|-----------------|
| | 4,5 | 6 | 9 | 14 | |
| Designed for max curtain(s) current | 4,5 A | 6 A | 9 A | 14 A | 14 A |
| Unit power supply | 230 V | | | | 230 V |
| Revolutions control levels | 0-1-2-3 | | | | 0-1-2-3-4-5 |
| IP rating | IP 20 | | | | IP 20 |
| Dimensions (length x width x height) | 300x400x170 mm | | | | 300x400x170 mm |

4. Function of the switchboard

- It allows use of all functions of the ECON controller to be described in a separate document.
- The variant for the units with AC fans may be controlled via ECON controller with 3-level fan revolutions setting option and 2-level heating setting.
- The variant for the units with EC fans may be controlled via ECON controller with 5-level fan revolutions setting option and 2-level heating setting.
- Output for control of electrothermic 2-way or 3-way 230V “NO” valve.
- Ready for possible connection of a spatial thermostat.
- Ready for control by a door contact.

5. Operation of the switchboard

- The ambient temperature must range between 10 and 35 °C.
- Designed for industrial environment.



Before any work with the unit, disconnect the electric power at the main circuit-breaker. Electric shock hazard!!

6. Decommissioning – disposal




After the expiration of the service life, the switchboard must be disassembled and disposed of. Only qualified company may disassemble the device. The product or components thereof must be disposed in environmentally-friendly manner at the end of its service life.

The components of the unit must be separated and sorted out by type of material for disposal. Dispose of the metal and plastic components at your local collection yard. The transport packaging of the product is made of common recyclable material (paper, polyethylene, wood) and is labelled as such according to ČSN 77 0052-2.

As far as disposal is concerned, it is operator's responsibility to comply with applicable national provisions in the country of use. In addition, follow regulations and laws of your country applicable to waste disposal. Separated collection and recycling of the products may help to protect environment and human health.

7. UNIREG – ECO-A switchboard wiring scheme



Kabely a jít, ní - Cables and protection - Kabeln und Schutz

| | | | |
|-----|----------|-------------------------|------------------------|
| FAO | B/16A/1p | UNIREG-ECON-AC 4.5A; 8A | UNIREG-ECON-AC 9A; 14A |
| W.1 | 3x0.75 | B/20A/1p | |
| W.2 | 3x0.75 | | |
| W.1 | 3x0.75 | | |
| W.2 | 3x0.75 | | |
| WS1 | 0.5x1.5 | | |
| WS2 | 0.5x1.5 | | |
| | 2x0.1 | | |


• Prírezy kabelů pletí so dĺky kabelu 50m. Typy kabelů, uvedené v dokumentácii, lze použiť pouze pro prostředí a za podmínek, daných výšecím kabelu.
 • Cable section are valid for the cable length to 50m. Cable types mentioned in the documentation, can be used by the cable producer, provided that the conditions of the environment and the conditions of the cable are met.
 • Unter Bedingungen benutzen, gegeben von dem Kabelhersteller.

Značení vodičů - Wire marking - Leiternkennung

| | | |
|---------------------------------|---------------------------------|--------------------------|
| (L) - AC/DC always voltage | (N) - AC/DC power conductor | (AC/DC) Hauptstromreise |
| (N) - AC "always" voltage | (AC) middle (reset) conductor | (Nulungse-) Mittelleiter |
| (PE) - schramný vodič | (SELV) - DC vodič malého napětí | (DC) small voltage |
| (SELV) - DC vodič malého napětí | (DC) small voltage | (DC) Steuerstromreise |

| | |
|----------------------------|---|
| Název - Name: | Provozniční UNIREG - Distribution board UNIREG - Schalttafel UNIREG |
| Regulator - Regler: | ECON TR |
| Kód - Code: | UNIREG-ECON-AC-WT-STIA-02 |
| Datum - Date: | 04/2022 |

8. UNIREG – ECO EC switchboard wiring scheme





STAVOKLIMA s.r.o.
Budějovická 450, 370 01 Homole
Tel.: +420 387 001 931
e-mail: info@stavoklima.cz
www.stavoklima.cz

